


10K Lift Check Valve

10SFBF
S.C.
FF-flanged



F-F dimension : JIS B 2011
End flanges : JIS B 2239 10K

120°C Static water..... 1.4MPa
220°C Steam, air, gas, oil..... 1.0MPa

●Use for lubricating or hydraulic oil is acceptable. Contact KITZ Corporation for technical advice, if valves are used as heat transfer media.

Materials

Parts	JIS material
Body	FCD-5
Cap	SUS403
Disc	SUS403
Body seat ring	SUS403


Dimensions

Size	mm						
	mm	15	20	25	32	40	50
	inch	1/2	3/4	1	1 1/4	1 1/2	2
L		85	95	110	130	150	180
H		39	42	48	56	65	73

NOTE : For flange dimensions, refer to Page 40. ※RF-flanged ends shall be optionally available.

10K Lift Check Valve

10SN
S.C.



E-E dimension : JV 4-4
End threads : JIS B 0203

120°C Static water..... 1.4MPa
220°C Steam, air, gas, oil..... 1.2MPa

●Use for lubricating or hydraulic oil is acceptable. Contact KITZ Corporation for technical advice, if valves are used as heat transfer media.

Materials

Parts	JIS material
Body	FCD-5
Bonnet	SCS13A / SUS304
Disc	SUS403
Body seat ring	SUS403
Gasket	C1100-0

Dimensions

Size	mm						
	mm	15	20	25	32	40	50
	inch	1/2	3/4	1	1 1/4	1 1/2	2
L		70	80	90	110	120	140
H		50	53	61	69	75	87