

Main parts and materials / Standards

Body / Bonnet / Disc	A216 WCB / A217WC6 / A217WC9 / A352LCB / A352LCC / A352LC1
	A351CF3 / A351CF3M / A351CF8 / A351CF8M
	A182F6 / A182F304 / A182F316 / A182F304L / A182F316L
Stem	A105+13Cr / A105+STL / A351CF8 / A351CF8M
Seating	A105+13Cr / A105+STL / A351CF8 / A351CF8M
Disc Ring	13Cr / STL / A351CF8 / CF8M
Design and Manufacture	API600, ANSIB16.34
Face to Face	ANSI B16.10
Flange End	ANSI B16.5
Inspection	API 598
Pressure-Temp Rating	ANSI B16.34

Z40/540/940H W/Y-150Lb	Inch	1.5	2	2.5	3	4	5	6	8	10	12	14	16	18	20	24	26	28	30	32	36	40	42	48	52
	DN	40	50	65	80	100	125	150	200	250	300	350	400	450	500	600	650	700	750	800	900	1000	1050	1200	1300
Z40/540/940H W/Y-300Lb	L	165	178	190	203	229	254	267	292	330	356	381	406	432	457	508	559	610	610	660	711	762	813	864	914
	Inch	1.5	2	2.5	3	4	5	6	8	10	12	14	16	18	20	24	26	28	30	32	36	40	42	48	
Z40/540/940H W/Y-600Lb	DN	40	50	65	80	100	125	150	200	250	300	350	400	450	500	600	650	700	750		900	1000	1050	1200	
	L	190	216	241	283	305	381	403	419	457	502	562	638	914	991	1143	1245		1346	1397		1727	1930	1981	2215
Z40/540/940H W/Y-900Lb	Inch	1.5	2	2.5	3	4	5	6	8	10	12	14	16	18	20	24		28	30		36	40	42		
	DN	40	50	65	80	100	125	150	200	250	300	350	400	450	500	600		700	750		900	1000	1050		
Z40/540/940H W/Y-1500Lb	L	241	292	330	356	432	508	559	660	787	838	889	991	1092	1194	1397		1549	1651		2083	2387	2438		
	Inch	1.5	2	2.5	3	4	5	6	8	10	12	14	16	18	20	24									
Z40/540/940H W/Y-2500Lb	DN	40	50	65	80	100	150		200	250	300	350	400	450	500	600									
	L	305	368	419	381	457	610		737	838	965	1029	1130	1219	1321	1549									
Z40/540/940H W/Y-1500Lb	Inch		2	2.5	3	4		6	8	10	12	14	16	18	20	24									
	DN		50	65	80	100		150	200	250	300	350	400	450	500	600									
Z40/540/940H W/Y-2500Lb	L		368	419	470	546		705	832	991	1130	1257	1384	1537	1664	1943									
	Inch		2	2.5	3	4		6	8	10	12														
	DN		50	65	80	100		150	200	250	300														
	L		451	508	578	673		914	1022	1270	1422														

API Globe Valve

Main parts and materials / Standards

Body/Bonnet/Disc	A216 WCB / A217WC6 / A217WC9 / A352LCC / A352LCC / A352LC1
	A351 CF3 / A351 CF3M / A351 CF8 / A351 CF8M
	A182F6 / A182F304 / A182F316 / A182F304L / A182F316L
Stem	A105+13Cr / A105+STL / A351CF8 / A351CF8M
Seating	A105+13Cr / A105+STL / A351CF8 / A351CF8M
Disc Ring	13Cr / STL / A351CF8 / CF8M
Design and Manufacture	BS1873, ANSIB16.34
Face to Face	ANSI B16.10
Flange End	ANSI B16.5
Inspection	API 598
Pressure-Temp Rating	ANSI B16.34

J41/541/941H/ W/Y-150Lb	Inch	1.5	2	2.5	3	4	5	6	8	10	12	14	16	18
	DN	40	50	65	80	100	125	150	200	250	300	350	400	450
J41/541/941H/ W/Y-300Lb	L	165	203	216	241	292	356	406	495	622	698	787	914	978
	Inch	1.5	2	2.5	3	4	5	6	8	10	12	14	16	
J41/541/941H/ W/Y-600Lb	DN	40	50	65	80	100	125	150	200	250	300	350	400	
	L	229	267	292	318	356	400	444	559	622	711	762	864	
J41/541/941H/ W/Y-900Lb	Inch	1.5	2	2.5	3	4	5	6	8	10	12	14	16	
	DN	40	50	65	80	100	125	150	200	250	300	350	400	
J41/541/941H/ W/Y-1500Lb	L	241	292	330	318	432	508	559	660	787	838	889	991	
	Inch	1.5	2	2.5	3	4	5	6	8	10	12	14	16	
J41/541/941H/ W/Y-2500Lb	DN	40	50	65	80	100	125	150	200	250	300	350	400	
	L	305	368	419	381	457	559	610	737	838	965	1029	1130	
	Inch		2	2.5	3	4		6	8	10	12	14	16	
	DN		50	65	80	100		150	200	250	300	350	400	
	L		368	419	470	546		705	832	991	1130	1257	1384	
	Inch		2	2.5	3	4		6	8	10	12			
	DN		50	65	80	100		150	200	250	300			
	L		451	508	578	673		914	1022	1270	1422			